

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



Alarm cable

Special combi alarm cable for security systems



Application : special combi cable for use alarm and security systems.

TECHNICAL DATA : TYPE ALARM

Construction of conductor : Highly flexible bare copper
0,5 mm² = 7 x 0,3 mm.
0,22 mm² = 7 x 0,2 mm.

Insulation of conductor : PVC 90°C.

Coding of conductors : 0,50 mm² = red and black.
0,22 mm² =

4 cores: white, orange, blue, green

6 cores: white, orange, blue, green, grey, brown

8 cores: white, orange, blue, green, grey, brown, yellow, violet

Shielding : Overall PP foil, a tinned drain wire 7 x 0,2 mm underneath.

Outer jacket : PVC 90°C.

Colour : white.

Copper resistance : 0,5 mm² : 38 Ohm/Km.
0,22 mm²: 92 Ohm/Km.

Capacitance : 100 nF/Km.

Temperature range : -5°C to +90°C.

Stock :

Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
0155151	2 x 0,5 + 4 x 0,22		5,8 mm
0155152	2 x 0,5 + 6 x 0,22		6,0 mm
0155153	2 x 0,5 + 8 x 0,22		6,6 mm