

Verbreeppark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



multi-conductor cable ARMAFLEX



Application : For flexible use in lighting fixtures.

TECHNICAL DATA : TYPE ARMAFLEX

Construction of conductor : Highly flexible, finely stranded wire, tinned copper, according to IEC 60228/5 and VDE 0295/5.

Insulation of conductor : Special TPE.

Coding of conductors : conductor 1: transparent.
 conductor 2: transparent with blue marking.
 conductor 3: transparent with brown marking

Outer jacket : Special PVC.

Colour of outer jacket : transparent.

Temperature range : Flexing: -5°C tot +70°C.

Static: -30°C tot +80°C.

Insulation resistance : Min 20 M. Ohm/km.

Test voltage : 2000 Volt.

Voltage rating : 300 Volt.

Stock :

Art.no.	Cores	Gage mm ²	Nominal O.D. mm
0100200	3 x	0,75	6,0
0100202	3 x	1,5	7,0