

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530

control cable BK



Application: : cable with two steel wires for traction relief for the suspension of control boxes.

TECHNICAL DATA : TYPE BK

Construction of conductor : flexible bare copper conductors according to VDE 0295/6.
 Insulation of conductor : special PVC compound TI 1/2 according to VDE 0281/part 1.
 Coding of conductors : black, numbered plus 1 yellow/green in outer layer.

gage mm ²	nr of litzes	diameter
1,5 mm ²	85	0,15

Outer jacket : special PVC compound, cold resistant.
 TM4 according to VDE 0281/part 1.

Colour of outer jacket : black.

Supporting elements : galvanised steel wire elements on both sides, with pvc sheath.

Bend radius : 12 x outer diameter.
 Temperature range : Flexing: -30°C - +70°C.
 Static: -40°C - +70°C.

Test voltage : 3000 Volt.
 Voltage rating : 300/500 Volt.
 Insulation resistance : 1,5 mm²: max.13,3 MOhm/km.

Stock :

Art.no.	cores x gage mm ²	outer diameter in mm
0145608	8 x 1,5	14,9 / 27,3
0145612	12 x 1,5	16,5 / 31,5
0145620	20 x 1,5	21,0 / 36,0
0145624	24 x 1,5	21,9 / 37,1