

Verbreeppark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



multi-conductor cable CK

unshielded computer cable



Application : Used as computer cable and in other data transmission systems. Flexible, twisted pairs.

TECHNICAL DATA : TYPE CK

Construction of conductor : Highly flexible, finely stranded, bare copper, according to VDE 0295/5. Twisted pairs.

Insulation of conductor : PVC, TI 1/2 according to VDE 0281/1.
Coding of conductors : Colour coding according to DIN 47100

Outer jacket : PVC, TI 1/2 according to VDE 0281/1.
Colour of outer jacket : PVC grey, RAL 7032.

Bend radius : 10 x outer diameter.
Temperature range : Flexing: -5°C tot +70°C.
Static: -30°C tot +70°C.

Insulation resistance : Min 20 M. Ohm/km.
Test voltage : 1200 Volt.
Voltage rating : 250 Volt.

Stock :

Art.no.	Cores	Gage mm ²	Nominal O.D. mm
0112002	2 x 2 x 0,14		5,0
0112003	3 x 2 x 0,14		5,3
0112006	6 x 2 x 0,14		6,7
0112015	15 x 2 x 0,14		9,5
0112025	25 x 2 x 0,14		11,5
0112030	30 x 2 x 0,14		12,4