

Verbreepark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530

lift cable CN

shielded



Application : lift cable for trailing cable installation, drag chains and as control cable in conveyor facilities, machine-tools.

TECHNICAL DATA : TYPE CN (STCN)

Construction of conductor : Flexible bare copper conductors according to VDE 0295/6.

Insulation of conductor : Rubber compound.

Coding of conductors : 6 conductors and more: black, numbered

Supporting element : central textile element and textile wrap around the cores.

Braiding : tinned copper braiding.

Outer jacket : Neoprene rubber compound.

Colour of outer jacket : blue or black.

Bend radius : 10 x outer diameter

Temperature range : Flexing: -25°C - +80°C.
 Static: -40°C - +80°C.

Test voltage : 3000 Volt.

Voltage rating : 300/500 Volt.

Stock :

Art.no.	cores x gage mm ²	outer diameter in mm	colour outer jacket	breaking load of suspension unit N
0142407	6 x 0,75	12,0	blue	1500
0142406	6 x 0,75	12,0	black	1500