

Verbreeppark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530

hook-up wire ESUY



TECHNICAL DATA

: TYPE ESUY

Construction of conductor : Highly flexible, extra finely stranded bare copper.
Insulation of conductor : PVC.

cross section mm ²	outer diameter mm	stranding number of wires x mm
0,5	2,0	132 x 0,07
0,75	2,2	195 x 0,07
1	2,5	260 x 0,07
1,5	3,5	192 x 0,10
2,5	3,8	320 x 0,10
4	5,0	512 x 0,10
6	6,5	768 x 0,10
10	7,5	1280 x 0,10
16	9,0	2048 x 0,10
25	10,5	3234 x 0,10
35	11,7	4508 x 0,10
50	14,7	6468 x 0,10
70	17,0	8967 x 0,10

Colours : black, transparent, yellow/green, red and blue.

Temperature range : flexing: -15°C to +80°C
static: -30°C to +80°C

Test Voltage : 3000 Volt.

Nominal Voltage : 0,5 to 1 mm² 500 V.
From 1,5 mm² 750 V.

Bend radius : flexing: 10 x cable diameter.
static: 6 x cable diameter.