

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



flatcable FCK PVC



Application : This cable is used in overhead transport systems. Special cold resistant PVC.

TECHNICAL DATA : TYPE FCK

Standards : VDE 0281, 0293, 0472, 0473.

Construction of conductor (1) : Highly flexible, finely stranded bare copper, according to VDE 0295/6.

Insulation of conductor (2) : PVC, TI 4 according to VDE 0281/1.

Coding of conductors : 1 conductor yellow/green the others black, numbered.

Outer jacket (4) : Special PVC TM 4 according to VDE 0281/1.

Colour of outer jacket : Black.

Bend radius : 10 x outer diameter

Temperature range : Flexing: -30°C tot + 70°C.

Static: -40°C tot + 70°C

Test voltage : 3000 Volt.

Voltage rating : 300/500 Volt.

Insulation resistance : Min. 100 MOhm/km.

Stock :

Art. no	Cores	Gage mm ²	height	width	Art. no	Cores	Gage mm ²	height	width
0138604	4 x 1,5		5,0	14,2	0138804	4 x 4		6,8	21,0
0138608	8 x 1,5		5,0	25,9	0138904	4 x 6		7,7	25,0
0138612	12 x 1,5		5,2	37,6	0138914	4 x 10		10,2	32,1
0138704	4 x 2,5		5,6	17,4	0138924	4 x 16		10,6	35,4
0138705	5 x 2,5		5,6	22,0					
0138707	7 x 2,5		5,6	29,2					
0138708	8 x 2,5		5,6	32,8					
0138712	12 x 2,5		6,0	47,6					