

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



hook up wire with Teflon

FEP or PTFE



TECHNICAL DATA

Construction of conductor : Highly flexible, finely constructed nickel-plated copper.
Insulation of conductor : FEP: -100°C to +200°C.
PTFE: -190°C to +260°C.

| Gage mm ² | Outer diameter: mm | Construction | Voltage rating |
|-------------------------|--------------------------|--------------|----------------|
| 0,50 | 1,24 | 15 x 0,203 | 600 Volt |
| 0,75 | 1,70 | 22 x 0,203 | 600 Volt |
| 1,00 | 1,88 | 29 x 0,203 | 600 Volt |
| 1,5 | 2,24 | 27 x 0,254 | 600 Volt |
| 2,5 | 2,65 | 45 x 0,254 | 600 Volt |

Stock

: FEP:

| Art.no. | Gage mm ² | Colour |
|---------|----------------------|--------|
| 0129605 | 1,5 | black |
| 0129702 | 2,5 | black |

PTFE:

| Art.no. | Gage mm ² | Colour |
|---------|----------------------|--------------|
| 0130951 | 0,5 | clear |
| 0130502 | 1 | yellow/green |
| 0130501 | 1 | grey |
| 0130603 | 1,5 | clear |
| 0130702 | 2,5 | yellow/green |
| 0130701 | 2,5 | clear |
| 0130703 | 2,5 | black |