

Verbreepark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



neoprene flat cable FN UL



Application : Flexible cable for use in trolley systems, transfer lines, machine-tools, hoisting devices, lifts, cranes and container bridges. Suitable for strongly bended and permanent moving applications. Durable and suitable for use indoor and outdoor.

TECHNICAL DATA : TYPE FN UL

Standard : UL Style 4540
 DIN VDE 0250, part 809

Construction of conductor : Highly flexible, finely stranded bare copper, according to VDE 0295/6
 Insulation of conductor : Rubber insulation
 Coding of conductors : according to HD 308 S2
 4 conductors: brown, black, grey and yellow/green
 5 conductors: brown, blue, grey, black and 1 yellow/green
 6 conductors and more: 1 conductor yellow/green other conductors black, numbered

Outer jacket : Neoprene
 Colour of outer jacket : Black
 Bend radius : 5 x outer diameter - height
 Temperature range : Flexing: -35°C to + 85°C
 Static: -40°C to + 85°C

Voltage rating : 600 Volt
 Test voltage : 2000 Volt

Stock	Art. no	Cores Gage mm ²	Dimensions height x width
	0137604	4 x 1,5	4,6 x 15,6 – 6,4 x 17,5
	0137608	8 x 1,5	4,6 x 28,3 – 7,8 x 35,0
	0137612	12 x 1,5	5,2 x 43,5 – 7,0 x 47,5
	0137704	4 x 2,5	5,8 x 18,7 – 7,8 x 21,0
	0137707	7 x 2,5	5,8 x 31,0 – 7,8 x 35,0
	0137708	8 x 2,5	5,8 x 35,0 – 7,8 x 39,0
	0137712	12 x 2,5	6,2 x 50,8 – 8,2 x 56,0
	0137804	4 x 4	7,1 x 21,8 – 9,1 x 26,0
	0137807	7 x 4	7,1 x 29,0 – 9,1 x 42,0
	0137904	4 x 6	7,9 x 24,9 – 9,9 x 29,0
	0137914	4 x 10	9,2 x 30,3 – 11,2 x 33,3
	0137924	4 x 16	11,0 x 35,7 – 13,0 x 38,0
	0137934	4 x 25	11,7 x 40,0 – 15,0 x 49,5