

Verbreeppark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



hook up wire H05/07V2-K + H05/07Z-K

harmonised hook up wire H05/07V2-K + halogen free version H05/07Z-K



TECHNICAL DATA :

TYPE H05/07V2-K

Standards : HD 21 (NEN 3621), <HAR>, KEMA, Lloyd's.
Construction of conductor : Highly flexible, finely constructed single wire,
bare copper, according to IEC 60228 class 5.
Insulation of conductor : PVC 90°C, short 105°C.

TYPE H05/07Z-K

Standards : HD 21 (NEN 3621), <HAR>, KEMA, Lloyd's.
Construction of conductor : Highly flexible, finely constructed single wire,
bare copper, according to IEC 60228 class 5.
Insulation of conductor : halogen free compound 90°C, low smoke.

Outer diameter	Gage in mm ²	Outer diameter in mm
	0,50	2,1 mm
	0,75	2,3 mm
	1,0	2,5 mm
	1,5	2,9 mm
	2,5	3,6 mm
	4	4,2 mm
	6	4,8 mm
	10	6,1 mm
	16	7,3 mm
	25	8,7 mm
	35	9,9 mm
	50	11,7 mm
	70	13,4 mm
	95	15,4 mm

Temperature : Flexing : -5°C tot +90°C
Bend radius : 4 x outer diameter.
Voltage rating : H05V2-K / H05Z-K: 300/500 Volt.
H07V2-K / H07Z-K: 450/750 Volt.

Test voltage : H05V2-K / H05Z-K: 2000 Volt.
H07V2-K / H07Z-K: 2500 Volt.

Colours : Various colours available from stock. Up to 6 mm² in 100 m lengths,
From 10 mm² available per meter.