

Verbreepark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## signal cable HH-ST KEMA

free of halogen



### TECHNICAL DATA

### :TYPE HH-ST

Standard : based on KEMA K 102-314.

Construction of conductor : Solid bare copper 0,8 mm  $\phi$ .  
Conductors : Paired.  
Insulation of conductor : halogen free compound, flame retardant.  
Coding of conductors : Colour coding according to NEN 1597.

Shielding : Overall aluminium foil, a tinned drain wire 0,8 mm underneath.

Outer jacket : halogen free compound, colour grey.

Voltage rating : 220 V.  
Test voltage : 1500 V.  
Copper resistance : 37,5 Ohm/Km.  
Capacitance : 100 nF/Km at 1000 Hz.  
Bend radius : 7,5 x outer diameter.  
Temperature range : -20°C to +70°C.

### Stock

:

Art.no.	Cores	Gage mm $\phi$	Nominal O.D. mm
0155002	1 x 2 x 0,8	grey	5,0
0155022	1 x 2 x 0,8	red	5,0
0155004	2 x 2 x 0,8	grey	7,0
0155006	3 x 2 x 0,8	grey	7,9
0155008	4 x 2 x 0,8	grey	8,6

Also available in red and blue.