

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



Jobarco Ecoflex type HHMB

Free of halogen, flame retardant



Application : **Flexible control cable for industrial and security installations, cable is completely halogen free. Low smoke and flame retardant. The material can be recycled and is eco-friendly.**

TECHNICAL DATA : **TYPE HHMB**

Construction of conductor : Highly flexible, finely stranded bare copper, according to VDE 0295/5.
Insulation of conductor : Halogen free compound, type TI6 acc. to HD 21.14 S1 annex A.
Coding of conductors : 2 conductors: black, numbered.
3 conductors and more: 1 conductor yellow/green in outer layer, other conductors black, numbered.

Outer jacket : Halogen free compound, type TM7 acc. to HD 21.14 S1 annex B, flame retardant.
Colour of outer jacket : Grey, RAL 7001.

Bend radius : 12.5 x outer diameter.
Temperature range : Flexing: -20°C to +70°C.
Static: -40°C to +70°C.
Insulation resistance : Min. 20 MOhm/km.

Test voltage : 3000 Volt.
Voltage rating : 0.5 t/m 1.5 mm²: 300/500 Volt.
10 mm²: 750 Volt.

Halogen free : according to IEC 60754-1.
Flame retardant : according to IEC 60332.3 cat. A.
Corrosive gasses : according to IEC 60754-2.

Verbreepark 15 NL-2731 BR Benthuisen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



HHMB

Art.no.	Cores	Gage mm ²	Nominal O.D. mm
0140302	2 x 0,5		4,8
0140303	3 x 0,5		5,1
0140304	4 x 0,5		5,5
0140307	7 x 0,5		6,8
0140402	2 x 0,75		5,4
0140403	3 x 0,75		5,7
0140404	4 x 0,75		6,2
0140405	5 x 0,75		6,8
0140407	7 x 0,75		7,8
0140412	12 x 0,75		10,5
0140418	18 x 0,75		12,0
0140502	2 x 1		5,6
0140503	3 x 1		6,1
0140504	4 x 1		6,7
0140505	5 x 1		7,5
0140506	6 x 1		8,0
0140507	7 x 1		8,0
0140508	8 x 1		9,5
0140512	12 x 1		10,7
0140518	18 x 1		12,7
0140525	25 x 1		15,4
0140530	30 x 1		16,2
0140534	34 x 1		17,2
0140542	42 x 1		19,2
0140602	2 x 1,5		6,4
0140603	3 x 1,5		6,8
0140604	4 x 1,5		7,6
0140605	5 x 1,5		8,3
0140607	7 x 1,5		9,1
0140612	12 x 1,5		12,4
0140618	18 x 1,5		14,4
0140625	25 x 1,5		16,8
0140634	34 x 1,5		19,6
0140703	3 x 2,5		8,9
0140704	4 x 2,5		9,7
0140707	7 x 2,5		12,0
0140712	12 x 2,5		15,0
0140804	4 x 4		10,9
0140904	4 x 6		12,8
0141004	4 x 10		17,9