

Verbreepark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



bus cable INSTABUS

free of halogen, for KNX/EIB Instabus systems



Application : special bus cable for use in KNX/EIB systems. This cable can easily be installed next to a 220 Volt power supply cable. For communication purposes between various Instabus equipment.

TECHNICAL DATA :TYPE Instabus

Construction of conductor : Solid bare copper 0,8 mm ϕ .
 Conductors : Paired.
 Insulation of conductor : PE, appr. 0.3 mm insulation thickness.
 Coding of conductors : black-red and white-yellow.

Shielding : Overall aluminium foil, a tinned drain wire 0,14 mm² (7x0,16mm) underneath.

Outer jacket : thermoplastic copolymer FRNC, colour green.

Voltage rating : 250 V.
 Test voltage : 1 min.: 4000 V.
 5 min.: 2500 V.

Copper resistance : 37,0 Ohm/Km.
 Capacitance : 90 pF/Km at 1000 Hz.

Bend radius : 20 x outer diameter.
 Temperature range : -40°C to +70°C.

Stock :

Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
0155100	2 x 2 x 0,8		6,6