

Verbreeppark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## installation cable INSTALFLEX

*flexible installation cable, YMVK-mb-ss*



**Application** : Flexible installation cable for low voltage, suitable for NEN 1010 areas. KEMA approved.

**TECHNICAL DATA** : TYPE INSTALFLEX YMVKmb-SS

Standards : HD 308 and KEMA K42, IEC 60332-3, IEC 60228.

Construction of conductor : Highly flexible, finely stranded bare copper, according to IEC 60228/5.

Insulation of conductor : XLPE.

Coding of conductor

: 1 conductor: black.  
2 conductors: blue, brown.  
3 conductors: brown, blue, yellow/green.  
4 conductors: brown, black, grey, yellow/green.  
5 conductors: brown, blue, black, grey, yellow/green.  
More than 5 conductors: 1 yellow/green,  
other conductors black, numbered.

Outer jacket : PVC, flame retardant.  
Petrol and oil resistant.

Colour of outer jacket : PVC grey.

Bend radius : 5 x outer diameter

Temperature range : Static: -20°C tot +70°C.

Test voltage : 3500 Volt.

Voltage rating : 600/1000 Volt.

***This cable is also available in a halogen free version: type YMzKmbzh-ss.***

Verbreeppark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## INSTALFLEX

Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm
0430102	1 x	16 qmm	9,5	0430401	4 x	10 qmm	19,1	0430501	5 x	10 qmm	19,6
0430103	1 x	25 qmm	11,2	0430402	4 x	16 qmm	20,6	0430502	5 x	16 qmm	22,6
0430104	1 x	35 qmm	12,5	0430403	4 x	25 qmm	26,1	0430503	5 x	25 qmm	28,6
0430105	1 x	50 qmm	13,9	0430404	4 x	35 qmm	30,1	0430504	5 x	35 qmm	32,1
0430106	1 x	70 qmm	16,1	0430405	4 x	50 qmm	33,4	0430505	5 x	50 qmm	35,5
0430107	1 x	95 qmm	18,1	0430406	4 x	70 qmm	38,0	0430506	5 x	70 qmm	41,2
0430108	1 x	120 qmm	20,3	0430407	4 x	95 qmm	42,7	0430507	5 x	95 qmm	47,1
0430109	1 x	150 qmm	22,6	0430408	4 x	120 qmm	47,1	0430508	5 x	120 qmm	51,8
0430110	1 x	185 qmm	24,8	0430409	4 x	150 qmm	51,5				
0430111	1 x	240 qmm	27,8	0430410	4 x	185 qmm	57,5				
0430112	1 x	300 qmm	30,7	0430411	4 x	240 qmm	65,0				

**See our Jobarcoflex type YK (non shielded) and YKO(shielded) for 1,5 qmm and 2,5 qmm.**