

Verbreepark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



instrumentation cable JPPDV-af

New version, without communication wire



TECHNICAL DATA : JPPDV-af

Standards : NEN-EN 50288-7.

Construction of conductor : soft-annealed, plain electrolytic copper, according to IEC60228, class 2 (7 threads).

Insulation of conductor : XLPE.

Pairs : 2 cores twisted into a pair.

Coding of conductors : white and black, numbered.

Shielding : 1 layer of polyester foil,
 1 layer of polyester/aluminium foil, with a tinned copper earth wire 7 x 0,31 mm f ,
 1 layer of polyester foil.

Inner jacket : PVC.

Armour : round or flat galvanised steel wires (depending on the cable diameter) and open-pattern counter wound galvanised steel strip.

Outer jacket : PVC, flame retardant, according to IEC60332-3-24 cat. C.

Colour of outer jacket : Black (BK) or blue (BU).

Voltage rating : 300 Volt.

Stock :

Article no.	type/colour	outer diameter	Article no.	type/colour	outer diameter
0199414	1 X 2 X 0,75 BU	10,5	0199662	1 X 2 X 1,3 BU	11,4
0199413	1 X 2 X 0,75 BK	10,5	0199676	1 X 2 X 1,3 BK	11,4
0199415	2 X 2 X 0,75 BU	13,4	0199664	2 X 2 X 1,3 BU	15,1
0199428	2 X 2 X 0,75 BK	13,4	0199678	2 X 2 X 1,3 BK	15,1
			0199665	4 X 2 X 1,3 BU	17,1
0199418	8 X 2 X 0,75 BU	17,6	0199667	8 X 2 X 1,3 BU	21,4
0199429	8 X 2 X 0,75 BK	17,6	0199687	8 X 2 X 1,3 BK	21,4
0199422	12 X 2 X 0,75 BU	20,9	0199688	12 X 2 X 1,3 BU	24,7
0199421	12 X 2 X 0,75 BK	20,9	0199689	12 X 2 X 1,3 BK	24,7
0199347	16 X 2 X 0,75 BK	23,2	0199690	16 X 2 X 1,3 BK	26,4
0199450	24 X 2 X 0,75 BK	26,8	0199672	24 X 2 X 1,3 BU	31,2
			0199692	24 X 2 X 1,3 BK	31,2