

Verbreepark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



instrumentation cable JPV-2af

New version, without communication wire



TECHNICAL DATA : JPV-2af

Standards : NEN-EN 50288-7.

Construction of conductor : soft-annealed, plain electrolytic copper, according to IEC60228, class 2 (7 threads).

Insulation of conductor : XLPE.

Pairs : 2 cores twisted into a pair.

Shielding of pairs : 1 layer of polyester foil,
 1 layer of polyester/aluminium foil, with a solid tinned copper earth wire 0,6 mm f,
 1 layer of polyester foil.

Coding of conductors : white and black, numbered.

Shielding : 1 layer of polyester foil,
 1 layer of polyester/aluminium foil, with a tinned copper drain wire 7 x 0,31 mm f,
 1 layer of polyester foil.

Outer jacket : PVC, flame retardant, according to IEC60332-3-24 cat. C.

Colour of outer jacket : Black (ZW) or blue (BL).

Voltage rating : 300 Volt.

Stock :

Article no.	type/ colour	outer diameter	Article no.	type/ colour	outer diameter	Article no.	type/ colour	outer diameter
0199042	2 X 2 X 0,5 BL	9,1	0199290	2 X 2 X 0,75 BL	9,8	0199539	2 X 2 X 1,3 BL	11,8
0199053	2 X 2 X 0,5 ZW	9,1	0199301	2 X 2 X 0,75 ZW	9,8	0199551	2 X 2 X 1,3 ZW	11,8
0199043	4 X 2 X 0,5 BL	10,4	0199291	4 X 2 X 0,75 BL	11,5	0199540	4 X 2 X 1,3 BL	13,9
0199054	4 X 2 X 0,5 ZW	10,4	0199302	4 X 2 X 0,75 ZW	11,5	0199554	4 X 2 X 1,3 ZW	13,9
0199045	8 X 2 X 0,5 BL	13,3	0199293	8 X 2 X 0,75 BL	14,7	0199542	8 X 2 X 1,3 BL	17,8
0199056	8 X 2 X 0,5 ZW	13,3	0199304	8 X 2 X 0,75 ZW	14,7	0199553	8 X 2 X 1,3 ZW	17,8
0199047	12 X 2 X 0,5 BL	15,9	0199295	12 X 2 X 0,75 BL	18,5	0199544	12 X 2 X 1,3 BL	22,2
0199058	12 X 2 X 0,5 ZW	15,9	0199305	12 X 2 X 0,75 ZW	18,5	0199555	12 X 2 X 1,3 ZW	22,2
0199048	16 X 2 X 0,5 BL	18,1						
			0199306	16 X 2 X 0,75 ZW	20,8	0199550	16 X 2 X 1,3 ZW	25,0
0199050	24 X 2 X 0,5 BL	21,9	0199298	24 X 2 X 0,75 BL	24,5	0199547	24 X 2 X 1,3 BL	29,7
0199061	24 X 2 X 0,5 ZW	21,9	0199309	24 X 2 X 0,75 ZW	24,5	0199558	24 X 2 X 1,3 ZW	29,7