

Verbreepark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



instrumentation cable JPV-af

New version, without communication wire



TECHNICAL DATA : JPV-af

Standards : NEN-EN 50288-7.

Construction of conductor : soft-annealed, plain electrolytic copper, according to IEC60228, class 2 (7 threads).

Insulation of conductor : XLPE.

Pairs : 2 cores twisted into a pair.

Coding of conductors : white and black, numbered.

Shielding : 1 layer of polyester foil,
 1 layer of polyester/aluminium foil, with a tinned copper earth wire 7 x 0,31 mm f , 1 layer of polyester foil.

Outer jacket : PVC, flame retardant, according to IEC60332-3-24 cat. C.

Colour of outer jacket : Black (ZW) or blue (BL).

Voltage rating : 300 Volt.

Stock :

Article no.	type/ colour	outer diameter	Article no.	type/ colour	outer diameter	Article no.	type/ colour	outer diameter
0199001	1 X 2 X 0,5 BL	5,6	0199248	1 X 2 X 0,75 BL	6,0	0199497	1 X 2 X 1,3 BL	6,9
0199021	1 X 2 X 0,5 ZW	5,6	0199261	1 X 2 X 0,75 ZW	6,0	0199509	1 X 2 X 1,3 ZW	6,9
0199002	2 X 2 X 0,5 BL	7,8	0199249	2 X 2 X 0,75 BL	8,7	0199498	2 X 2 X 1,3 BL	10,4
0199022	2 X 2 X 0,5 ZW	7,8	0199262	2 X 2 X 0,75 ZW	8,7	0199511	2 X 2 X 1,3 ZW	10,4
0199003	4 X 2 X 0,5 BL	9,1	0199250	4 X 2 X 0,75 BL	9,9	0199499	4 X 2 X 1,3 BL	12,2
0199023	4 X 2 X 0,5 ZW	9,1	0199263	4 X 2 X 0,75 ZW	9,9	0199510	4 X 2 X 1,3 ZW	12,2
0199005	8 X 2 X 0,5 BL	11,6	0199252	8 X 2 X 0,75 BL	12,7	0199501	8 X 2 X 1,3 BL	15,6
0199025	8 X 2 X 0,5 ZW	11,6	0199260	8 X 2 X 0,75 ZW	12,7	0199512	8 X 2 X 1,3 ZW	15,6
0199007	12 X 2 X 0,5 BL	13,8	0199251	12 X 2 X 0,75 BL	16,3	0199503	12 X 2 X 1,3 BL	19,7
0199027	12 X 2 X 0,5 ZW	13,8	0199267	12 X 2 X 0,75 ZW	16,3	0199514	12 X 2 X 1,3 ZW	19,7
0199254	16 X 2 X 0,5 BL	15,5	0199255	16 X 2 X 0,75 BL	18,2			
0199253	16 X 2 X 0,5 ZW	15,5	0199256	16 X 2 X 0,75 ZW	18,2	0199516	16 X 2 X 1,3 ZW	22,1
0199010	24 X 2 X 0,5 BL	18,5	0199257	24 X 2 X 0,75 BL	21,4			
0199030	24 X 2 X 0,5 ZW	18,5	0199270	24 X 2 X 0,75 ZW	21,4	0199517	24 X 2 X 1,3 ZW	26,2
						0199525	1 X 3 X 1,3 BL	7,3
						0199513	1 X 3 X 1,3 ZW	7,3