

Verbreeppark 15 NL-2731 BR Benthuizen  
 Postbus 183 NL-2700 AD Zoetermeer  
 Telefoon (079) 331 93 13\*  
 Fax (079) 342 35 72  
 E-mail info@jobarco.com  
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
 45.73.01.031  
 IBAN NL17ABNA0457301031  
 BIC ABNANL2A  
 Postbank 233083  
 K.v.K. Leiden nr. 28058530

## lift cable LSTN



**Application** : lift cable for trailing cable installation, drag chains and as control cable in conveyor facilities, machine-tools.

**TECHNICAL DATA** : TYPE LSTN

Construction of conductor : Flexible bare copper conductors according to VDE 0295/6.

Insulation of conductor : Rubber compound.

Coding of conductors : 3 conductors: brown, blue, yellow/green.  
 4 conductors: brown, blue, black, yellow/green.  
 5 conductors: brown, blue, 2 x black, yellow/green.  
 6 conductors and more: black, numbered plus 1 yellow/green in outer layer.

Supporting element : central textile element and textile wrap around the cores.

Outer jacket : Neoprene rubber compound.

Colour of outer jacket : black.

Bend radius : 10 x outer diameter

Temperature range : Flexing: -25°C - +70°C.

Static: -40°C - +70°C.

Test voltage : 3000 Volt.

Voltage rating : 450/750 V.

Stock :

Art.no.	cores x gage mm <sup>2</sup>	outer diameter in mm	Art.no.	cores x gage mm <sup>2</sup>	outer diameter in mm
0133503	3 x 1	9,0	0133612	12 x 1,5	21,0
0133507	7 x 1	13,5	0133618	18 x 1,5	22,0
0133512	12 x 1	19,5	0133624	24 x 1,5	25,0
0133518	18 x 1	20,0			
0133524	24 x 1	22,5			
0133536	36 x 1	27,0	0133704	4 x 2,5	12,5
			0133705	5 x 2,5	14,5
0133603	3 x 1,5	9,5	0133707	7 x 2,5	17,5
0133604	4 x 1,5	11,5	0133712	12 x 2,5	26,0
0133607	7 x 1,5	13,5			
0133609	9 x 1,5	16,5			