

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



hook up wire MS

PVC insulation



TECHNICAL DATA : TYPE MS (0.14 mm² - 95 mm²)

Construction of conductor : Highly flexible, finely constructed single wire,
bare copper, according to VDE 0295/5
Insulation of conductor : PVC.

Gage mm ²	outer diameter mm	construction	Gage mm ²	outer diameter mm	construction
0,14	1,0	18 x 0,10	10	6,2	78 x 0,40
0,25	1,4	14 x 0,15	16	7,9	120 x 0,40
0,34	1,5	7 x 0,25	25	10,1	192 x 0,40
0,50	2,1	16 x 0,20	35	11,1	266 x 0,40
0,75	2,3	24 x 0,20	50	13,3	399 x 0,40
1,00	2,5	32 x 0,20	70	15,3	551 x 0,40
1,5	3,0	32 x 0,24	95	16,6	722 x 0,40
2,5	3,6	52 x 0,24			
4	4,2	52 x 0,30			
6	4,8	78 x 0,30			

Temperature : Flexing : -25°C tot +70°C

Colours : Various colours available from stock.
Up to 2.5 mm² in 100 m lengths,
From 4 mm² available per meter.

Double colours : Minimum order quantity 3000 meters.

Voltage rating : 0,14 to 0,34 mm² 250 V.
0,5 to 1 mm² 300/500 V.
1,5 to 95 mm² 450/750 V.

Halogen free wire : see page 1.23

UL/CSA wire : see page 1.24