

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



telecom cable PTT N45 + N45 ZH

telecom cable according to Dutch KPN standard N45, in PVC or halogen free version



Application : signal and control cable for telecom purposes for indoor use.

TECHNICAL DATA : TYPE N45 (pvc) or N45 ZH (halogen free)

Standard : N45, K102.

Construction of conductor : Solid bare copper 0,5 mm ϕ .

Conductors : Paired.

Insulation of conductor : **N45** PVC 0,22 mm thick, **N45 ZH** halogen free compound.

Coding of conductors : Colour coding according to NEN 1597.

Drain wire : solid copper 0,7 mm,
N45 transparent PVC insulation, **N45 ZH** halogen free compound .

Outer jacket : **N45** PVC flame retardant, colour grey, rip cord underneath.
N45 ZH halogen free, flame retardant, colour grey, rip cord underneath.

Bend radius : 15 x outer diameter.

Voltage rating : 60 V.

Test voltage : 2000 V.

Copper resistance 20 °C : 96,2 Ohm/Km.

Capacitance : 100 nF/Km.

Stock :

	Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
N45	0165105	5 x 2 x 0,5		6,0
	0165110	10 x 2 x 0,5		8,5
	0165116	16 x 2 x 0,5		10,0
	0165120	20 x 2 x 0,5		10,5
	0165125	25 x 2 x 0,5		12,5
	0165130	30 x 2 x 0,5		13,0
	0165140	40 x 2 x 0,5		14,5
N45 ZH	0165305	5 x 2 x 0,5		6,0
	0165310	10 x 2 x 0,5		8,5
	0165320	20 x 2 x 0,5		10,5