

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



telecom cable PTT N88

telecom cable according to Dutch KPN standard N88



Application : signal and control cable for telecom purposes for indoor use. Also suitable for ISDN applications.

TECHNICAL DATA :TYPE N88

Standard : N88, K102.

Construction of conductor : Solid bare copper 0,5 mm ϕ .

Conductors : each 4 cores in a star quad.

Insulation of conductor : PE, 0,32 mm thick.

Coding of conductors : red, white, blue, orange.

Drain wire : solid copper 0,8 mm PE insulation.

In case of 1 star quad, the drain wire is 0,5 mm.

Outer jacket : PVC flame retardant, colour grey, rip cord underneath.

Bend radius : 15 x outer diameter.

Voltage rating : 60 V.

Test voltage : 2000 V.

Copper resistance 20°C : 93 Ohm/Km.

Capacitance : 38 nF/Km.

Stock :

Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
0166101	1 x 4 x 0,5		4,4
0166105	5 x 4 x 0,5		9,3
0166110	10 x 4 x 0,5		12,4
0166115	15 x 4 x 0,5		14,1
0166120	20 x 4 x 0,5		16,9
0166130	30 x 4 x 0,5		19,3
0166150	50 x 4 x 0,5		23,6