

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530

telecom cable PTT N92

telecom cable according to Dutch KPN standard N92



Application : signal and control cable for telecom purposes for indoor use. Also suitable for ISDN applications and direct burial.

TECHNICAL DATA : TYPE N92 (GPEW)

Standard : N92.

Construction of conductor : Solid bare copper 0,5 mm ϕ .
 Conductors : each 4 cores in a star quad.
 Insulation of conductor : PE, 0,4 mm thick.
 Coding of conductors : red, white, blue, orange.
 Water stop : primary water stop.
 Shielding/ water barrier : overlapping folded aluminium shield, 4 tinned copper wires along sided underneath the shield.
 Inner jacket : PE jacket, adhered with the aluminium shield.
 Armour : bare steel wires in an elastic foam bedding
 Outer jacket : PE, colour green.

Bend radius : 15 x outer diameter.
 Voltage rating : 60 V.
 Test voltage : 2000 V.
 Copper resistance 20°C : 93 Ohm/Km.
 Capacitance : 38 nF/Km.

Stock :

Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
0167701	1 x 4 x 0,5		12,5
0167702	6 x 4 x 0,5		16,8
0167704	12 x 4 x 0,5		18,9
0167705	15 x 4 x 0,5		21,1
0167706	25 x 4 x 0,5		25,2
0167707	50 x 4 x 0,5		32,2