

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530

reeling cable NSHTOU



Application : Reeling cables are used for high mechanical stress situations, especially for applications with frequent winding and unwinding with simultaneous tensile and tensional stress, for building machinery, conveyors and cranes.

TECHNICAL DATA : TYPE NSHTOU

Construction of conductor : Flexible tinned copper conductors according to VDE 0295/5.

Insulation of conductor : Rubber compound.

Coding of conductors : 4 conductors: brown, blue, black, yellow/green.

5 conductors: brown, blue, 2 x black, yellow/green.

6 conductors and more: black, numbered plus 1 yellow/green in outer layer.

Outer jacket : Neoprene rubber compound sheath with textile braid embedded for torsion protection.

Colour of outer jacket : black.

Bend radius : \varnothing between 12 and 20 mm: 4 x outer diameter

Temperature range : Flexing: -25°C - +80°C.

Static: -40°C - +80°C.

Test voltage : 2500 Volt.

Voltage rating : 0,6/1 kV.

Stock :

Art.no.	cores x gage mm ²	outer diameter in mm	weight kg/km
0185604	4 x 1,5	16,0	290
0185607	7 x 1,5	20,5	485
0185612	12 x 1,5	23,5	650
0185618	18 X 1,5	27,5	910
0185624	24 x 1,5	31,0	1105
0185704	4 x 2,5	18,0	380
0185705	5 x 2,5	20,5	490
0185712	12 x 2,5	27,5	910
0185724	24 x 2,5	35,5	1580
0185804	4 x 4	21,0	535
0185904	4 X 6	23,5	705
0185914	4 x 10	28,5	1045
0185934	4 x 25	36,5	1985