

Verbreepark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



HOOK UP WIRE NVS

Flexible, to +350 °C



Application : wiring of heating elements, cartridges, bands and hot plates.
Furnaces and industrial ovens, domestic electrical heating appliances.

TECHNICAL DATA : TYPE NVS

Standards : VERITAS certificate BV 153552, DIN 17753, DIN 17740, ASTM B160.

Construction of conductor : Flexible nickel core, type 200.
Insulation of conductor : - silicone-impregnated glass lappings.
- silicone-coated fibreglass braid.

Colour : brown, other colours on request.

Characteristics : good resistance to thermal shock, ageing and usual chemical atmospheres.

Temperature range : -60 °C tot +350 °C, peaks at +400 °C.
Voltage rating : 300/500 Volt.
Test Voltage : 2000 Volt.

Stock :

Art.no.	Gage mm ²		Nominal O.D. mm
0130001	1 QMM BRUIN	14 x 0,30	2,5
0130002	1,5 QMM BRUIN	21 x 0,30	2,8
0130003	2,5 QMM BRUIN	35 x 0,30	3,2
0130004	4 QMM BRUIN	56 x 0,30	4,3
0130005	6 QMM BRUIN	84 x 0,30	4,8
0130006	10 QMM BRUIN	140 x 0,30	6,8