

Verbreepark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



reeling cable PRO-H

New generation highly flexible reeling cable



Application : cable for heavy machinery such as conveyor facilities, fork lift trucks, train engines and agricultural machines. Suitable for outdoor use. Very good UV and ozone resistant, good oil resistant, flame retardant and good wear resistant.

TECHNICAL DATA : TYPE PRO-H

Core : Aramid fibre.

Construction of conductor : flexible bare copper conductors according to VDE 0295/5.

Insulation of conductor : halogen free polypropylene.

Coding of conductors : according to VDE 0293-308:

4 cores: brown, black, grey, yellow/green.

5 cores: blue, brown, black, grey, yellow/green.

6 cores and more: black, numbered plus 1 yellow/green in outer layer.

Supporting element : Aramid fibre in the core and textile wrapping around the conductors.

Outer jacket : Polyurethan, black.
 Halogen free, adhesion free.
 Oil resistant, wear and tear resistant.
 Flame retardant according to VDE 0482-332-2-2.

Bend radius : 7.5 x outer diameter

Temperature range : Flexing: -25°C - +90°C.

Static: -40°C - +90°C.

Test voltage : 3000 Volt.

Voltage rating : 600 Volt.

Stock	Art.no.	cores x gage mm ²	outer diameter in mm (+/- 0.5 mm)
	0169110	12 x 1,5	17,4
	0169104	4 x 2,5	11,5
	0169106	5 x 2,5	12,4