

Verbreepark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



multi-conductor cable TRIOFLEX-CY

<HAR>, UL and CSA approved



Application : Flexible cable, copper braided. Protects against electromagnetic interference (EMI). For export uses.

TECHNICAL DATA : TYPE TRIOFLEX-CY

Standards : According to <HAR>, UL/CSA Style 2587.

Construction of conductor : Highly flexible, finely stranded bare copper, according to VDE 0295/5.

Insulation of conductor : PVC according to VDE 0281/1.

Coding of conductors : 2 conductors: black, numbered.
 3 conductors and more: 1 conductor yellow/green in outer layer, other conductors black, numbered.

Braiding : Tinned copper braiding.

Outer jacket : PVC TM 1/2 according to VDE 0281/1.

Colour of outer jacket : PVC grey, RAL 7001.

Oil resistance : according to VDE 0281/13 and HD 21.13S1.

Bend radius : 15 x outer diameter

Temperature range : Flexing: -5°C tot +90°C.
 Static: -30°C tot +90°C.

Insulation resistance : Min 20 M. Ohm/km.

Voltage rating : UL/CSA 600 Volt, <HAR> 300/500 Volt.

Stock :

Art.no.	Cores	Gage	Nominal O.D.	Art.no.	Cores	Gage	Nominal O.D.	Art.no.	Cores	Gage	Nominal O.D.
		mm ²	mm			mm ²	mm			mm ²	mm
1316302	2 x 0,5		8,0	1316402	2 x 0,75		8,4	1316502	2 x 1		8,7
1316303	3 x 0,5		8,4	1316403	3 x 0,75		8,8	1316503	3 x 1		9,3
1316304	4 x 0,5		8,9	1316404	4 x 0,75		9,6	1316504	4 x 1		9,9
1316305	5 x 0,5		9,7	1316405	5 x 0,75		10,3	1316505	5 x 1		10,9
1316307	7 x 0,5		11,3	1316407	7 x 0,75		12,2	1316507	7 x 1		12,9
1316312	12 x 0,5		13,7	1316412	12 x 0,75		14,5	1316512	12 x 1		15,4
1316318	18 x 0,5		15,6	1316418	18 x 0,75		16,9	1316518	18 x 1		17,7
1316325	25 x 0,5		18,0	1316425	25 x 0,75		19,6	1316525	25 x 1		20,4
1316334	34 x 0,5		20,5	1316434	34 x 0,75		22,1				