

Verbreepark 15 NL-2731 BR Benthuizen  
 Postbus 183 NL-2700 AD Zoetermeer  
 Telefoon (079) 331 93 13\*  
 Fax (079) 342 35 72  
 E-mail info@jobarco.com  
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
 45.73.01.031  
 IBAN NL17ABNA0457301031  
 BIC ABNANL2A  
 Postbank 233083  
 K.v.K. Leiden nr. 28058530



## multi-conductor cable UL-LIYY

According to UL Style 2570, 80 °C, 600 Volt



**Application** : For flexible use in industrial environments, machine manufacturing, process control systems. Especially for export purposes to the USA and/or other countries.

**TECHNICAL DATA** : TYPE UL-LIYY

Standards : UL 2570.

Construction of conductor : Highly flexible, finely stranded bare copper, according to VDE 0295/5.

Insulation of conductor : PVC.

Coding of conductors : 2 conductors: black, numbered.  
 3 conductors and more: 1 conductor yellow/green in outer layer, other conductors black, numbered.

Outer jacket : PVC special warmth resistant compound.

Colour of outer jacket : PVC grey, RAL 7001.

Flame retardant : IEC 332/1. 1993-04.

Bend radius : 15 x outer diameter

Temperature range : Flexing: -5°C tot +80°C.  
 Static: -30°C tot +80°C.

Insulation resistance : Min 20 M. Ohm/km.

Test voltage : 2000 Volt.

Voltage rating : 600 Volt.

Stock :

Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm
1205502	2 x 1		6,8	1205604	4 x 1,5		8,5
1205503	3 x 1		7,1	1205625	25 x 1,5		19,6
1205504	4 x 1		7,8	1205703	3 x 2,5		9,7
1205505	5 x 1		9,0	1205704	4 x 2,5		10,8
1205508	8 x 1		11,4	1205804	4 x 4		13,9
1205512	12 x 1		12,5				