

Verbreeppark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



multi-conductor cable UL-LIYYSY

According to UL Style 1581, 80 °C, 600 Volt, steel wire shielded



Application

: **Steel wire shielded cable for flexible use in industrial environments, machine manufacturing, process control systems. Especially for export purposes to the USA and/or other countries.**

TECHNICAL DATA

: **TYPE UL-LIYYSY**

Standards

: UL 2570.

Construction of conductor

: Highly flexible, finely stranded bare copper, according to VDE 0295/5.

Insulation of conductor

: PVC, UL 1011.

Coding of conductors

: black with numbers, from 3 cores with yellow/green.

Inner jacket

: PVC special warmth resistant compound.

Braiding

: galvanized steel wire braiding.

Outer jacket

: PVC special warmth resistant and oil resistant compound.

Outer jacket colour

: PVC grey, RAL 7001.

Flame retardant

: IEC 332/1. 1993-04.

Bend radius

: 15 x outer diameter

Temperature range

: Flexing: -5°C tot +80°C.
Static: -30°C tot +80°C.

Insulation resistance

: Min 20 M. Ohm/km.

Test voltage

: 2000 Volt.

Voltage rating

: 300 Volt.

Stock

:
Art.no. Cores Gage Nominal
O.D.
mm2 mm
9560001 5 x 6 18,7