

Verbreepark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



signal cable WDK + WDK MBZH

signal cable, multicore, solid cores. PVC or halogen free



TECHNICAL DATA

Construction of conductor
 Insulation of conductor
 Coding of conductors

:TYPE WDK + WDK MBZH

: Solid bare copper 0,8 mm ϕ .
 : PVC (WDK) or halogen free compound (WDK MBZH).
 : Colour coding according to NEN 1597.

Outer jacket
 Colour outer jacket

: PVC flame retardant (WDK) or halogen free compound (WDK MBZH).
 : grey or red.

Voltage rating
 Test voltage
 Copper resistance
 Capacitance
 Temperature range

: 300 V.
 : 1500 V.
 : 37,5 Ohm/Km.
 : 120 nF/Km.
 : -20°C to +70°C.

Stock

:

	Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm	Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
WDK	0163302	2 x	0,8 grey	4,5	0163310	10 x	0,8 grey	7,8
	0162302	2 x	0,8 red	4,5	0163312	12 x	0,8 grey	8,0
	0163303	3 x	0,8 grey	4,7	0162312	12 x	0,8 red	8,0
	0163304	4 x	0,8 grey	5,0	0163316	16 x	0,8 grey	8,8
	0163306	6 x	0,8 grey	5,9	0163320	20 x	0,8 grey	9,5
	0163308	8 x	0,8 grey	6,8	0162314	20 x	0,8 red	9,5
					0163324	24 x	0,8 grey	10,1
					0163330	30 x	0,8 grey	11,7
WDK MBZH	0164305	2 x	0,8 grey mbzh	4,5				
	0164405	2 x	0,8 red mbzh	4,5				
	0164307	4 x	0,8 grey mbzh	5,0				
	0164306	6 x	0,8 grey mbzh	5,9				
	0164310	8 x	0,8 grey mbzh	6,8				
	0164308	10 x	0,8 grey mbzh	7,8				
	0164309	12 x	0,8 grey mbzh	8,0				