

Verbreeppark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## installation cable XMVK

lightweight installation cable 450/750 Volt



**Application** : lightweight installation cable with improved properties for low Voltage 450/750 Volt, suitable for NEN 1010 areas. KEMA approved.

**TECHNICAL DATA** : TYPE XMVK

Standard : KEMA K 42 C-07.  
Construction of conductor : solid bare electrolytic copper.  
Insulation of conductor : XLPE.  
Coding of conductor : 2 conductors: blue, brown.  
3 conductors: brown, blue, yellow/green.  
4 conductors: brown, black, grey, yellow/green.  
5 conductors: brown, blue, black, grey, yellow/green.  
More than 5 conductors: 1 yellow/green,  
other conductors black, numbered.

Outer jacket : PVC.  
Petrol and oil resistant.

Colour of outer jacket : PVC grey, RAL 7001.

Temperature range : Flexing: -20 - +70°C.

Test voltage : 2500 Volt.

Voltage rating : 450/750 Volt.

Stock :

Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm
0401010	2 x	1,5	8,1	0401015	2 x	2,5	8,8
0401020	3 x	1,5	8,4	0401021	3 x	2,5	9,2
0401040	4 x	1,5	9,3	0401141	4 x	2,5	10,1
0401041	5 x	1,5	9,8	0401142	5 x	2,5	10,8