

Verbreeppark 15 NL-2731 BR Benthuizen
Postbus 183 NL-2700 AD Zoetermeer
Telefoon (079) 331 93 13*
Fax (079) 342 35 72
E-mail info@jobarco.com
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
45.73.01.031
IBAN NL17ABNA0457301031
BIC ABNANL2A
Postbank 233083
K.v.K. Leiden nr. 28058530



installation cable YK

flexible installation cable



Application : **Flexible installation cable for low voltage, suitable for NEN 1010 areas. KEMA approved.**

TECHNICAL DATA : **TYPE YK**

Standard : KEMA K 151-4.
Construction of conductor : Highly flexible, finely stranded bare copper, according to VDE 0295/5.
Insulation of conductor : PVC.
Coding of conductor : 2 conductors: blue, brown.
3 conductors: brown, blue, yellow/green.
4 conductors: brown, black, grey, yellow/green.
5 conductors: brown, blue, black, grey, yellow/green.
More than 5 conductors: 1 yellow/green, other conductors black, numbered.
Outer jacket : PVC.
Petrol and oil resistant.
Colour of outer jacket : PVC grey, RAL 7001.
Bend radius : 10 x outer diameter
Temperature range : Flexing: -5°C tot +70°C.
Static: -30°C tot +70°C.
Voltage rating : 450/750 Volt.

Stock

Art.no.	Cores	Gage mm ²	Nominal O.D. mm	Art.no.	Cores	Gage mm ²	Nominal O.D. mm
0108602	2 x 1,5		9,0	0108702	2 x 2,5		10,6
0108603	3 x 1,5		11,2	0108703	3 x 2,5		12,5
0108604	4 x 1,5		12,2	0108704	4 x 2,5		13,5
0108605	5 x 1,5		13,0	0108705	5 x 2,5		14,7
0108607	7 x 1,5		14,0	0108707	7 x 2,5		15,8
0108608	8 x 1,5		15,2	0108712	12 x 2,5		20,3
0108612	12 x 1,5		17,8	0108715	15 x 2,5		22,5
0108615	15 x 1,5		19,6	0108720	20 x 2,5		24,8
0108620	20 x 1,5		21,6	0108725	25 x 2,5		28,1
				0108625	25 x 1,5		24,4
				0108634	34 x 1,5		27,2