

Verbreeppark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## installation cable VO-YmvKas mb

*Steel wire braided, KEMA approved*



**Application** : **Installation cable for direct burial, steel wire braided, flame retardant, KEMA approved.**

**TECHNICAL DATA** : **TYPE VO-YmvKas mb**

Standard : KEMA K 42-1-4-D, HD 604-4-D, NEN 3617.

Construction of conductor : Solid bare copper according to IEC 60228/1 and 2.

Insulation of conductor : XLPE.

Coding of conductors : 1 conductor: black.  
2 conductors: blue, brown.  
3 conductors: black, brown, grey.  
4 conductors: blue, brown, black, grey.  
5 conductors: blue, brown, 2 black, grey.  
More than 5 conductors: all conductors black, numbered.

Inner jacket : PVC, grey.

Braiding : Steel wire braiding.

Outer jacket : PVC flame retardant.

Colour of outer jacket : grey.

Test voltage : 3500 Volt

Voltage rating : 600/1000 Volt.

Verbreeppark 15 NL-2731 BR Benthuisen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## VO-YMvKas mb

Art.no.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art. No.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm
0411102	2 x 1,5		13,1	0411104	2 x 2,5		13,9
0411120	3 x 1,5		13,5	0411121	3 x 2,5		14,4
0411140	4 x 1,5		14,2	0411141	4 x 2,5		14,9
0411160	5 x 1,5		15,0	0411161	5 x 2,5		16,1
0411170	6 x 1,5		15,3	0411180	6 x 2,5		16,4
0411190	7 x 1,5		15,3	0411192	7 x 2,5		16,4
0411200	8 x 1,5		16,2	0411202	8 x 2,5		17,3
0411210	10 x 1,5		19,0	0411238	10 x 2,5		20,8
0411220	12 x 1,5		18,5	0411237	12 x 2,5		20,0
0411230	14 x 1,5		19,4	0411231	14 x 2,5		20,8
0411232	16 x 1,5		19,9	0411243	16 x 2,5		21,4
0411233	19 x 1,5		20,7	0411234	19 x 2,5		22,6
0411235	24 x 1,5		23,5	0411236	24 x 2,5		25,7
0411242	30 x 1,5		24,8	0411239	30 x 2,5		27,0
0411246	37 x 1,5		26,2				
0411105	2 x 4		15,1	0411125	2 x 6		16,2
0411122	3 x 4		15,5	0411123	3 x 6		16,8
0411142	4 x 4		16,5	0411143	4 x 6		17,8
0411162	5 x 4		17,6	0411163	5 x 6		19,0
0411245	7 x 4		17,9				
0411107	2 x 10		18,6				
0411124	3 x 10		19,4				
0411144	4 x 10		20,5				

Verbreeppark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## installation cable VG-YmvKas mb

steel armoured, KEMA approved



<b>Application</b>	<b>: Installation cable for direct burial, steel wire braided, flame retardant, KEMA approved.</b>
<b>TECHNICAL DATA</b>	<b>: TYPE VG-YmvKas mb</b>
Standard	: KEMA-keur K 42-1-4-D, HD 604-4-D, NEN 3617.
Construction of conductor	: Solid bare copper.
Insulation of conductor	: XLPE.
Coding of conductors	: 1 conductor: black. 2 conductors: blue, brown. 3 conductors: black, brown, grey. 4 conductors: blue, brown, black, grey. 5 conductors: blue, brown, 2 black, grey. More than 5 conductors: all conductors black, numbered.
Inner jacket	: PVC, grey.
Armour	: round or flat galvanised steel wire combined with copper wire and an open counter-spiral of galvanised steel.
Outer jacket	: PVC flame retardant.
Colour of outer jacket	: grey.
Test voltage	: 3500 Volt
Voltage rating	: 600/1000 Volt.

Verbreeppark 15 NL-2731 BR Benthuizen  
 Postbus 183 NL-2700 AD Zoetermeer  
 Telefoon (079) 331 93 13\*  
 Fax (079) 342 35 72  
 E-mail info@jobarco.com  
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
 45.73.01.031  
 IBAN NL17ABNA0457301031  
 BIC ABNANL2A  
 Postbank 233083  
 K.v.K. Leiden nr. 28058530



## VG-YMvKas mb

Art. No.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm	Art. No.	Cores	Gage mm <sup>2</sup>	Nominal O.D. mm
xxx	1 x	50	20,0	0411124	3 x	10	20,4
0411240	1 x	70	22,5	0411127	3 x	16	22,5
xxx	1 x	95	24,0	0411128	3 x	25	26,7
xxx	1 x	120	26,0	0411119	3 x	35	29,2
0411001	1 x	150	28,0	0411132	3 x	50	28,0
xxx	1 x	185	28,0	0411129	3 x	70	31,5
xxx	1 x	240	33,5	0411130	3 x	95	36,5
xxx	1 x	300	36,0	0411133	3 x	120	40,0
xxx	1 x	400	40,0	0411134	3 x	150	42,5
0411107	2 x	10	19,6	0411151	3 x	185	42,5
0411131	2 x	16	21,7	0411126	3 x	240	55,0
0411144	4 x	10	21,5	0411164	5 x	10	25,5
0411147	4 x	16	24,3	0411165	5 x	16	27,5
0411145	4 x	25	28,7	0411167	5 x	25	33,0
0411146	4 x	35	32,1	0411168	5 x	35	36,0
0411152	4 x	50	32,0	0411169	5 x	50	41,0
0411150	4 x	70	36,0				
0411155	4 x	95	40,0				
0411148	4 x	120	44,5				
0411135	4 x	150	50,0				
0411156	4 x	185	50,0				
0411149	4 x	240	63,0				