

Verbreepark 15 NL-2731 BR Benthuizen  
 Postbus 183 NL-2700 AD Zoetermeer  
 Telefoon (079) 331 93 13\*  
 Fax (079) 342 35 72  
 E-mail info@jobarco.com  
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
 45.73.01.031  
 IBAN NL17ABNA0457301031  
 BIC ABNANL2A  
 Postbank 233083  
 K.v.K. Leiden nr. 28058530



## signal cable YY-ST 0,6 MM

Signal cable, foil shielded, cores 0.6 mm solid



### TECHNICAL DATA

### :TYPE YY-ST

Construction of conductor : Solid bare copper 0,6 mm  $\phi$ .  
 Conductors : Paired.  
 Insulation of conductor : PVC  
 Coding of conductors : Colour coding according to NEN 1597.  
 Shielding : Overall aluminium foil, a tinned drain wire underneath.  
 Outer jacket : PVC , colour grey.  
 Conductor : 0,6 mm  $\phi$   
 Voltage rating : 300 V.  
 Test voltage : 1500 V.  
 Copper resistance : 65 Ohm/Km.  
 Temperature range : -20°C to +70°C.

### Stock

Art.no.	Cores	Gage mm $\phi$	Nominal O.D. mm
0157204	2 x 2	x 0,6	6,0
0157206	3 x 2	x 0,6	7,1
0157208	4 x 2	x 0,6	7,5
0157216	8 x 2	x 0,6	8,8
0157220	10 x 2	x 0,6	9,4
0157224	12 x 2	x 0,6	10,3
0157232	16 x 2	x 0,6	11,5
0157240	20 x 2	x 0,6	13,4
0157260	30 x 2	x 0,6	15,4
0157291	50 x 2	x 0,6	19,4

Also available in red and blue, contact our sales department for the availability.