

Verbreeppark 15 NL-2731 BR Benthuizen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



signal cable YY-ST KEMA



TECHNICAL DATA

:TYPE YY-ST

Construction of conductor : Solid bare copper 0,6/0,8 mm ϕ .
 Conductors : Paired.
 Insulation of conductor : PVC
 Coding of conductors : Colour coding according to NEN 1597.
 Shielding : Overall aluminium foil, a tinned drain wire underneath.
 Outer jacket : PVC , colour grey.
 Conductor : 0,8 mm ϕ
 Voltage rating : 220 V.
 Test voltage : 1500 V.
 Copper resistance : 37,5 Ohm/Km.
 Capacitance : 120 nF/Km at 1000 Hz.
 Temperature range : -20°C to +70°C.

Stock

Art.no.	Cores	Gage mm ϕ	Nominal O.D. mm
0158602	1 x 2 x 0,8		4,8
<i>The 1 x 2 x 0,8 does not have a KEMA approval.</i>			
0158604	2 x 2 x 0,8		6,8
0158606	3 x 2 x 0,8		7,3
0158608	4 x 2 x 0,8		7,8
0158610	5 x 2 x 0,8		8,8
0158612	6 x 2 x 0,8		9,2
0158616	8 x 2 x 0,8		10,1
0158620	10 x 2 x 0,8		11,2
0158624	12 x 2 x 0,8		11,8
0158630	15 x 2 x 0,8		13,6
0158640	20 x 2 x 0,8		14,6
0158650	25 x 2 x 0,8		16,9
0158660	30 x 2 x 0,8		17,8
0158680	40 x 2 x 0,8		21,0

Also available in red and blue, contact our sales department for the availability.