

Verbreepark 15 NL-2731 BR Benthuisen
 Postbus 183 NL-2700 AD Zoetermeer
 Telefoon (079) 331 93 13*
 Fax (079) 342 35 72
 E-mail info@jobarco.com
 Internet www.jobarco.com

Bank ABN-AMRO Amsterdam
 45.73.01.031
 IBAN NL17ABNA0457301031
 BIC ABNANL2A
 Postbank 233083
 K.v.K. Leiden nr. 28058530



signal cable YY-Z-ST KEMA



TECHNICAL DATA

: TYPE YY-Z-ST KEMA

Standard

: KEMA K102-315.

Construction of conductor

: Solid bare copper 0,8 mm f .

Insulation of conductor

: PVC

Coding of conductors

: Colour coding according to NEN 1597.

Braiding

: Overall aluminium foil, a tinned drain wire (0.8 mm) underneath.
 Galvanized steel wire braiding (80% coverage)
 between inner (PVC) and outer jacket.

Outer jacket

: PVCmb (mb=flame retardant), colour grey or green.

Voltage rating

: 300 V.

Test voltage

: 1500 V.

Copper resistance

: 37,5 Ohm/Km.

Capacitance

: 120 nF/Km bij 1000 Hz.

Temperature range

: -20°C to +70°C.

Stock

: Art.no	Cores	Gage mm	Nominal O.D. mm	Colour
0158902	1 x 2 x 0,8		8,6	grey
0158904	2 x 2 x 0,8		10,6	grey
0158906	3 x 2 x 0,8		11,0	grey
0158908	4 x 2 x 0,8		11,6	grey
0158910	5 x 2 x 0,8		12,6	grey
0158912	6 x 2 x 0,8		13,0	grey
0158920	10 x 2 x 0,8		14,9	grey
0158924	12 x 2 x 0,8		15,7	grey
0158932	16 x 2 x 0,8		17,8	grey
0158948	24 x 2 x 0,8		20,3	grey
0159102	1 x 2 x 0,8		8,6	green
0159104	2 x 2 x 0,8		10,6	green
0159106	3 x 2 x 0,8		11,0	green
0159108	4 x 2 x 0,8		11,6	green
0159112	6 x 2 x 0,8		13,0	green
0159116	8 x 2 x 0,8		14,5	green

Also available in red and blue for some types, please contact our sales department for the possibilities.