

Verbreepark 15 NL-2731 BR Benthuizen  
Postbus 183 NL-2700 AD Zoetermeer  
Telefoon (079) 331 93 13\*  
Fax (079) 342 35 72  
E-mail info@jobarco.com  
Internet www.jobarco.com

Bank ABN-AMRO Amsterdam  
45.73.01.031  
IBAN NL17ABNA0457301031  
BIC ABNANL2A  
Postbank 233083  
K.v.K. Leiden nr. 28058530



## signal cable YY KEMA



### TECHNICAL DATA

:TYPE YY

Standard : Kema K102-313.

Construction of conductor : Solid bare copper 0,8 mm  $\phi$ .  
Conductors : Paired.  
Insulation of conductor : PVC  
Coding of conductors : Colour coding according to NEN 1597.

Outer jacket : PVC flame retardant , colour grey.

Bend radius : 7,5 x outer diameter.  
Voltage rating : 220 V.  
Test voltage : 1500 V.  
Copper resistance : 37,5 Ohm/Km.  
Capacitance : 120 nF/Km at 1000 Hz.  
Temperature range : -20°C to +70°C.

Stock :

Art.no.	Cores	Gage mm $\phi$	Nominal O.D. mm
0158504	2 x 2 x 0,8		6,5
0158506	3 x 2 x 0,8		7,1
0158508	4 x 2 x 0,8		7,8
0158510	5 x 2 x 0,8		8,6
0158550	25 x 2 x 0,8		16,8