

## Control cable Armaflex T



|   |  |
|---|--|
| <b>Application</b>                                    | <b>: For flexible use in lighting fixtures. This type has a steel wire for strain relief (max. weight 80 kg).</b>            |
| <b>TECHNICAL DATA</b>                                 | <b>: 0100203</b>   |
| <b>Remarks</b>  | <b>: Cores colour coded: 1 core transparent, 1 core with brown identification wire, 1 core with blue identification wire</b> |
| Dimension   | : 3 x 1,5  |
| Conductor category                                    | : Class 5 = flexible   |
| Stranding element                                     | : No   |
| Conductor material                                    | : Cu, tinned   |
| Core insulation                                       | : Other  |
| Core identification                                   | : Colour   |
| Protective conductor                                  | : No   |
| Inner sheath  | : No   |
| Screen over stranding element                         | : None   |
| Screen over stranding                                 | : None   |
| Material outer sheath                                 | : PVC  |
| Colour outer sheath                                   | : Transparent  |
| Halogen free (acc. EN 60754-1/2)                      | : No   |
| Flame retardant                                       | : No   |
| Low smoke (acc. EN 61034-2)                           | : No   |
| Low temperature resistant (acc. EN 60811-504+505+506) | : No   |
| Oil resistant (acc. EN 60811-404)                     | : No   |
| Outer diameter approx.                                | : 7.5mm  |
| Permitted cable outer temperature, in movement        | : -5°C to 70°C   |
| Permitted cable outer temperature, fixed              | : -30°C to 80°C  |
| Nominal voltage U                                     | : 300V   |
| Core protecton  | : No   |