

## Control cable Camerakabel CAM-CC-SWB



|   |  |
|---|--|
| <b>Application</b>                                    | : Flexible combi cable for use in security systems, such as camera surveillance systems. Suitable for direct burial. |
| <b>TECHNICAL DATA</b>                                 | : <b>0100314</b>   |
| <b>Remarks</b>  | : <b>4 flexible cores + 1 x coax 75 Ohm</b>  |
| Dimension   | : 4 x 0,75   |
| Conductor category                                    | : Class 5 = flexible   |
| Stranding element                                     | : No   |
| Conductor material                                    | : Cu, bare   |
| Core insulation                                       | : Copolymer, thermoplastic   |
| Core identification                                   | : Colour   |
| Protective conductor                                  | : No   |
| Inner sheath  | : No   |
| Screen over stranding element                         | : None   |
| Screen over stranding                                 | : None   |
| Material outer sheath                                 | : PVC  |
| Colour outer sheath                                   | : Black  |
| Halogen free (acc. EN 60754-1/2)                      | : No   |
| Flame retardant                                       | : In accordance with EN 60332-1-2  |
| Low smoke (acc. EN 61034-2)                           | : No   |
| Low temperature resistant (acc. EN 60811-504+505+506) | : No   |
| Oil resistant (acc. EN 60811-404)                     | : No   |
| Outer diameter approx.                                | : 14.2mm   |
| Permitted cable outer temperature, in movement        | : -5°C to 70°C   |
| Permitted cable outer temperature, fixed              | : -30°C to 70°C  |
| Nominal voltage U                                     | : 500V   |
| Bending radius  | : 192mm  |
| Core protecton  | : No   |