

Control cable Camerakabel CAM-CC



Application : Flexible combi cable for use in security systems, such as camera surveillance systems.

TECHNICAL DATA : TYPE CAM-CC

Remarks : 2 flexible cores + 1 x coax 75 Ohm

| | |
|---|-----------------------------------|
| Conductor category | : Class 5 = flexible |
| Stranding element | : No |
| Conductor material | : Cu, bare |
| Core insulation | : Copolymer, thermoplastic |
| Core identification | : Colour |
| Protective conductor | : No |
| Inner sheath | : No |
| Screen over stranding element | : None |
| Screen over stranding | : None |
| Material outer sheath | : PVC |
| Colour outer sheath | : Black |
| Halogen free (acc. EN 60754-1/2) | : No |
| Flame retardant | : In accordance with EN 60332-1-2 |
| Low smoke (acc. EN 61034-2) | : No |
| Low temperature resistant (acc. EN 60811-504+505+506) | : No |
| Oil resistant (acc. EN 60811-404) | : No |
| Permitted cable outer temperature, in movement | : -5°C to 70°C |
| Permitted cable outer temperature, fixed | : -30°C to 70°C |
| Nominal voltage U | : 500V |
| Core protecton | : No |

| ProductNr | Dimension | Outer diameter approx. (mm) | Bending radius (mm) |
|-----------|-----------|-----------------------------------|------------------------|
|-----------|-----------|-----------------------------------|------------------------|

| ProductNr | Dimension | Outer diameter approx. (mm) | Bending radius (mm) |
|-----------|-----------|-----------------------------------|------------------------|
| 0100112 | 2 x 0,75 | 11 | 165 |
| 0100113 | 3 x 0,75 | 11.1 | 167 |
| 0100114 | 4 x 0,75 | 11.6 | 174 |