

Control cable Stuurflex CY ZWART



Application	: Flexible cable, copper braided. Protects against electromagnetic interference. Colour coded acc. to DIN47100.
TECHNICAL DATA	: 0114105
Remarks	: Nice flexible PVC with excellent characteristics: Tensile strength 18 N/mm ² and elasticity 323%. Grey=RAL7001, Blue=RAL5015.
Dimension	: 5 x 0,25
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: Braiding
Material outer sheath	: PVC
Colour outer sheath	: Black
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Outer diameter approx.	: 5.5mm
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No