

## Control cable EQ-flex CC-O



<b>Application</b>	<b>: For flexible use in industrial environments, machine manufacturing, process control systems.</b>
<b>TECHNICAL DATA</b>	<b>: TYPE CC-O</b>
<b>Remarks</b>	<b>: Cores colour coded according to DIN47100. Oil resistant according to EN 50290-2-22 (TM54).</b>
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Colour
Protective conductor	: No
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: PVC
Colour outer sheath	: Grey
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Permitted cable outer temperature, in movement	: -15°C to 70°C
Permitted cable outer temperature, fixed	: -40°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No
Euro fire class acc. to EN 13501-6	: Eca

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
1007302	2 x 0,5	5	72
1007303	3 x 0,5	5.3	76
1007304	4 x 0,5	5.7	82
1007305	5 x 0,5	6.3	94
1007307	7 x 0,5	6.8	102
1007412	12 x 0,75	10.1	150