

## Control cable EQ-flex CY-JZ



**Application** : Flexible cable, copper braided. Protects against electromagnetic interference.

**TECHNICAL DATA** : TYPE CY-JZ

**Remarks** : Oil resistant according to EN 50290-2-22 (TM54).

Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: Braiding
Material outer sheath	: PVC
Colour outer sheath	: Grey
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Permitted cable outer temperature, in movement	: -5°C to 70°C
Permitted cable outer temperature, fixed	: -30°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No
Euro fire class acc. to EN 13501-6	: Eca

ProductNr	Dimension	Outer diameter approx. (mm)
1017303	3 x 0,5	5.7
1017304	4 x 0,5	6.3
1016308	8 x 0,5	8.8
1017312	12 x 0,5	9.6
1017403	3 x 0,75	6.3
1017404	4 x 0,75	6.9
1017405	5 x 0,75	7.5
1016606	7 x 0,75	8.2
1016608	8 x 0,75	8.6
1016610	10 x 0,75	10.3
1017412	12 x 0,75	10.7
1017418	18 x 0,75	12.5
1017425	25 x 0,75	14.8
1017434	34 x 0,75	16.8
1017503	3 x 1	6.7
1017504	4 x 1	7.3
1017505	5 x 1	8
1017507	7 x 1	8.5
1017512	12 x 1	11.4
1017518	18 x 1	13.7
1017603	3 x 1,5	7.4
1016637	4 x 1,5	8.1
1017605	5 x 1,5	8.9
1017607	7 x 1,5	9.8
1017612	12 x 1,5	12.9
1017625	25 x 1,5	17.8
1017703	3 x 2,5	8.9
1017704	4 x 2,5	9.8
1017705	5 x 2,5	10.7
1017804	4 x 4	12
1017904	4 x 6	14.2
1017950	4 x 10	17.2
1017305	x	