

Single core cable Jobwire ESUY



Application	: Highly flexible hook-up wire with highly stranded cores.
TECHNICAL DATA	: TYPE ESUY
Remarks	: Highly flexible core construction. For example: 1.5 mm ² = 385 x 0,07 mm bare copper litzes. For comparison: class 6 = 80 x 0,15 mm. Green RAL 6018/yellow RAL 1021:30%/70%.
Conductor material	: Cu, bare
Conductor category	: Class 6 = very flexible
Core insulation	: PVC
Screen	: No
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -15°C to 80°C
Permitted cable outer temperature, fixed	: -30°C to 80°C
Nominal voltage U	: 750V

ProductNr	Dimension	Core colour	Outer diameter approx. (mm)
0136123	0,5	Blue	2
0136214	1,5	Black	2.9
0136101	2,5	Black	3.8
0136201	2,5	Green/yellow	3.8
0136200	2,5	Red	3.8
0136111	4	Black	5
0136103	6	Black	6.5
0136203	6	Green/yellow	6.2
0136202	6	Transparent	6.5
0136104	10	Black	7.5
0136204	10	Green/yellow	7.5
0136114	16	Black	9
0136205	16	Green/yellow	9
0136206	25	Green/yellow	10.5