

## Control cable Ecoflex CPR HCH-JZ Cca



**Application** : Flexible control cable for industrial and security installations, cable is completely halogenfree. Low smoke and flame retardant acc. to IEC 60332-1-2 and IEC 60332-3-24. The material can be recycled and is eco-friendly.

**TECHNICAL DATA** : TYPE HCH-JZ Cca

Standards : CPR

**Remarks** : Ozone resistant acc. to EN50396. CPR class Cca.

Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: Polyolefin
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: Braiding
Material outer sheath	: Polyolefin
Colour outer sheath	: Blue
Halogen free (acc. EN 60754-1/2)	: Yes
Flame retardant	: In accordance with EN 60332-3-24
Low smoke (acc. EN 61034-2)	: Yes
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -15°C to 70°C
Permitted cable outer temperature, fixed	: -40°C to 70°C
Nominal voltage U	: 500V
Core protecton	: No
Euro fire class acc. to EN 13501-6	: Cca
Euro class smoke generation	: s1a
Euro class flaming droplets	: d0 (no flaming droplets/particles)
Euro class acidity level	: a1

ProductNr	Dimension	Outer diameter approx. (mm)
0184122	4 x 0,75	6.5
0184125	7 x 0,75	7.4
0184127	12 x 0,75	9.6