

## Control cable Highflex PRO CC UL



<b>Application</b>	: Suitable for use in cable chain systems. The keen construction makes the cable extremely flexible and applicable in various continuous moving equipment. The cable has a diminutive bend radius which makes it possible to use it in minuscule spaces. With UL approval.
<b>TECHNICAL DATA</b>	: TYPE PRO CC UL
Standards	: UL 21530
<b>Remarks</b>	: Very good petrol and oil resistant. Sea water resistant. Halogen free. Colour jacket is petrol blue.
Conductor category	: Class 6 = very flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: Copolymer, thermoplastic
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: No
Screen over stranding element	: None
Screen over stranding	: None
Material outer sheath	: Copolymer, thermoplastic
Colour outer sheath	: Other
Halogen free (acc. EN 60754-1/2)	: Yes
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Permitted cable outer temperature, in movement	: -25°C to 90°C
Permitted cable outer temperature, fixed	: -40°C to 90°C
Nominal voltage U	: 600V
No. bending cycles	: 3000000
Core protection	: No

Outer diameter

ProductNr	Dimension	approx. (mm)	Bending radius (mm)
0169204	7 x 0,5	7.1	54
0169205	4 x 1,5	7.5	57