

## Data cable Highflex PRO CKY 2D



**Application** : Suitable for use in cable chain systems. The keen construction makes the cable extremely flexible and applicable in various continuously moving equipment. The cable has a diminutive bend radius which makes it possible to use it in small spaces.

**TECHNICAL DATA** : TYPE PRO CKY 2D

**Remarks** : Very good petrol and oil resistant. Sea water resistant. Halogen free. Colour jacket is petrolblue.

Stranding element : Pairs  
 Conductor material : Cu, bare  
 Conductor category : Class 6 = very flexible  
 Core insulation : Polypropylene  
 Core identification : Colour  
 Screen over stranding element : None  
 Screen over stranding : Braiding  
 Material outer sheath : Other  
 Colour outer sheath : Other  
 Halogen free (acc. EN 60754-1/2) : Yes  
 Flame retardant : No  
 Low smoke (acc. EN 61034-2) : No  
 Permitted cable outer temperature, in movement : -25°C to 90°C  
 Permitted cable outer temperature, fixed : -40°C to 90°C

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)	Number of stranding elements
0169060	2 x 2 x 0,25	6.6	42	2
0169062	4 x 2 x 0,25	8	52	4
0169063	8 x 2 x 0,25	11	71	8