

Single core cable Jobwire MS



Application : Flexible hook-up wire for use in junction boxes, apparatus and machinery.

TECHNICAL DATA : TYPE MS

Remarks : Type MS is available starting from 0,14 mm².

Conductor material	: Cu, bare
Conductor category	: Class 5 = flexible
Core insulation	: PVC
Screen	: No
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: No
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: No
Permitted cable outer temperature, in movement	: -25°C to 70°C
Permitted cable outer temperature, fixed	: -25°C to 70°C
Nominal voltage U	: 250V

ProductNr	Dimension	Core colour	Outer diameter approx. (mm)
0146002	0,14	Blue	1
0146003	0,14	Brown	1
0146014	0,14	Green/yellow	1
0146006	0,14	Grey	1
0146012	0,14	White	1
0146113	0,25	Green/yellow	1.4
0146205	0,34	Brown	1.5
0146202	0,34	Orange	1.5
0146201	0,34	Pink	1.5
0146214	0,34	Purple/violet	1.5
0146215	0,34	Transparent	1.5
0146208	0,34	Yellow	1.5