

Power cord Jobspiral SP-ASS



TECHNICAL DATA

: TYPE SP-ASS

Conductor material	: Cu, bare
Connection 1	: Socket outlet with protective contact, angled
Nominal voltage	: 500V
Spiralized cable	: Yes
Protective conductor	: Yes
With cord switch	: No

ProductNr	Dimension	Length (m)	Material outer sheath	Temperature resistance (°C)	Colour outer sheath	Oil resistant (acc. EN 60811-404)
0291001	3 x 0,75	0.5	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290001	3 x 0,75	0.5	PVC	-5°C to 70	Black	No
0290002	3 x 0,75	0.5	PVC	-5°C to 70	White	No
0291005	3 x 0,75	0.75	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290007	3 x 0,75	0.75	PVC	-5°C to 70	Black	No
0290008	3 x 0,75	0.75	PVC	-5°C to 70	White	No
0291002	3 x 1	0.5	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290003	3 x 1	0.5	PVC	-5°C to 70	Black	No
0290004	3 x 1	0.5	PVC	-5°C to 70	White	No
0291006	3 x 1	0.75	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290009	3 x 1	0.75	PVC	-5°C to 70	Black	No
0290010	3 x 1	0.75	PVC	-5°C to 70	White	No
0291003	3 x 1,5	0.5	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290005	3 x 1,5	0.5	PVC	-5°C to 70	Black	No
0290006	3 x 1,5	0.5	PVC	-5°C to 70	White	No
0291007	3 x 1,5	0.75	PUR (Polyurethane)	-30°C to 90	Black	Yes
0290011	3 x 1,5	0.75	PVC	-5°C to 70	Black	No
0290012	3 x 1,5	0.75	PVC	-5°C to 70	White	No
0291009	3 x 1,5	1	PUR (Polyurethane)	-30°C to 90	Black	Yes
0291004	3 x 2,5	0.5	PUR (Polyurethane)	-30°C to 90	Black	Yes
0291008	3 x 2,5	0.75	PUR (Polyurethane)	-30°C to 90	Black	Yes