

Control cable UL LIYYCY-JZ



Application	: Flexible cable, copper braided. Protects against electromagnetic interference.
TECHNICAL DATA	: TYPE LIYYCY-JZ
Standards	: UL 2587; CSA AWM IA/B IIA/B
Remarks	: Outer jacket colour=RAL7001.
Conductor category	: Class 5 = flexible
Stranding element	: No
Conductor material	: Cu, bare
Core insulation	: PVC
Core identification	: Numbers
Protective conductor	: Yes
Inner sheath	: Yes
Screen over stranding element	: None
Screen over stranding	: Braiding
Material outer sheath	: PVC
Colour outer sheath	: Grey
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Low temperature resistant (acc. EN 60811-504+505+506)	: No
Oil resistant (acc. EN 60811-404)	: Yes
Permitted cable outer temperature, in movement	: -5°C to 90°C
Permitted cable outer temperature, fixed	: -40°C to 90°C
Nominal voltage U	: 600V
Core protecton	: No

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
-----------	-----------	-----------------------------	---------------------

ProductNr	Dimension	Outer diameter approx. (mm)	Bending radius (mm)
1217804	4 x 4	15.3	91
1217904	4 x 6	16.8	100