

Signal-/telecommunications cable Jobsignal YY-ST 06



Application : Signal and control cable for use in intercom, telephone and security appliances.

TECHNICAL DATA : TYPE YY-ST 06

Standards : KEMA K 102-314

Remarks : Colour code according to NEN1597. Outer jacket PVCmb.

Conductor category	: Class 1 = solid
Conductor material	: Cu, bare
Stranding	: Bundle
Stranding element	: Pairs
Core insulation	: PVC
Core identification	: Colour
Screen over stranding element	: None
Screen over stranding	: Foil
Longitudinal water blocking	: No
Radial water blocking	: No
Protective sheath	: No
Armouring	: No
Material outer sheath	: PVC
Colour outer sheath	: Grey
Halogen free (acc. EN 60754-1/2)	: No
Flame retardant	: In accordance with EN 60332-1-2
Low smoke (acc. EN 61034-2)	: No
Circuit integrity	: No
Permitted cable outer temperature, fixed	: -20°C to 70°C
Outdoor use permitted	: No

ProductNr	Dimension	Outer diameter approx. (mm)
-----------	-----------	-----------------------------

ProductNr	Dimension	Outer diameter approx. (mm)
0157204	2 x 2 x 0,6	6
0157206	3 x 2 x 0,6	7.1
0157208	4 x 2 x 0,6	7.5
0157216	8 x 2 x 0,6	8.8
0157220	10 x 2 x 0,6	9.4